

<b>Max. Outside diameter</b>	400 mm																		
<b>Suitable subsoils</b>	<ul style="list-style-type: none"> <li>■ Solid walls ≥ 100 mm</li> <li>■ Penetration seals ≥ 2 x 50 mm</li> </ul>							<ul style="list-style-type: none"> <li>■ Drywall partitions ≥ 100 mm</li> <li>■ Shaft walls ≥ 2 x 20 mm</li> </ul>						<ul style="list-style-type: none"> <li>■ Solid ceilings ≥ 150 mm</li> </ul>					
<b>Suitable insulations</b>	<ul style="list-style-type: none"> <li>■ Synthetic rubber insulation ≤ 43 mm</li> <li>■ PE-acoustic insulation ≤ 5 mm</li> </ul>																		
<b>Suitable pipes</b>	<ul style="list-style-type: none"> <li>■ Geberit Silent-PP</li> <li>■ Georg Fischer COOL-FIT</li> <li>■ Plastic composite pipes with aluminium inset ≤ 1,5 mm</li> <li>■ PE-HD</li> <li>■ PP</li> </ul>							<ul style="list-style-type: none"> <li>■ POLO-KAL NG</li> <li>■ POLO-KAL XS</li> <li>■ PVC</li> <li>■ REHAU RAUPIANO PLUS</li> <li>■ REHAU RAUPIANO LIGHT</li> <li>■ Wavin SiTech</li> </ul>											

<b>Collar dimensions (mm)</b>	32	40	50	63	75	90	110	125	140	160	180	200	225 MAX	250 MAX	280 MAX	300 MAX	315 MAX	350 MAX	400 MAX
<b>Pipe's inner diameter (mm)</b>	36	44	54	67	79	94	114	129	144	165	184	204	239	264	289	314	328	364	414
<b>Pipe's outer diameter (mm)</b>	50	58	68	94	106	132	155	172	200	220	264	284	328	353	378	403	417	453	503
<b>Component height (mm)</b>	26	26	26	26	26	26,6	26,6	40	40	40	40	40	50	50	50	50	50	50	50
<b>No. of fixing tabs (pcs)</b>	2	2	2	4	4	4	4	4	6	6	8	8	10	10	12	12	12	12	12